



AMERICAN MINING CONGRESS TURNOUT DATA

Turnout Data for 30-in. Gage (continued) Heavy Rail – 70-lb. to 80-lb. ASCE rail, inclusive

American Mining Congress Standards

Frog						Switch					Actual Lead	Closure Rails			
No.	Angle	Type	Rail Weight	Point	Actual Toe Length	Length	Angle	Point	Heel Spread	Vertex Distance		Curved			Straight
												Radius	MO	Length	Length
3	18°55'29"	Cast RBF	70 to 80 70 to 80	1/2" 1/2"	9-1/2" 31"	7'6" 7'6"	3°35'00" 3°35'00"	3/8" 3/8"	6" 6"	6" 6"	16'7" 16'7"	30'0" 30'0"	3-5/8" 2-5/16"	8' 6-3/4" 6'9-1/4"	8'3-1/2" 6'6"
4	14°15'00"	Cast RBF	70 to 80 70 to 80	1/2" 1/2"	12-1/2" 40"	7'6" 7'6"	3°35'00" 3°35'00"	3/8" 3/8"	6" 6"	6" 6"	20'0" 20'0"	55'0" 55'0"	3-11/16" 2-3/8"	11'7'-15/16" 9'4-7/16"	11'5-1/2" 9'2"
5	11°25'16"	Cast RBF	70 to 80 70 to 80	1/2" 1/2"	15-11/16" 42-1/2"	10'0" 10'0"	2°41'12" 2°41'12"	3/8" 3/8"	6" 6"	8" 8"	25'0" 25'0"	87'0" 87'0"	3-5/16" 2-5/16"	13'10-1/4" 11'7'-9/16"	13'8-5/16" 11'5-1/2"
6	9°31'38"	Cast RBF	70 to 80 70 to 80	1/2" 1/2"	18-13/16" 45"	10'0" 10'0"	2°41'12" 2°41'12"	3/8" 3/8"	6" 6"	8" 8"	27'6" 27'6"	130'0" 130'0"	3" 2-1/4"	16'0-7/8" 13'10-3/4"	15'11-3/16" 13'9"

Note: W.P.F. denotes "Welded Plate Frog."

Turnout Data for 36-in. Gage Light Rail – 20-lb to 60-lb ASCE rail, inclusive

American Mining Congress Standards

Frog						Switch					Actual Lead	Closure Rails			
No.	Angle	Type	Rail Weight	Point	Actual Toe Length	Length	Angle	Point	Heel Spread	Vertex Distance		Curved			Straight
												Radius	MO	Length	
2	28°04'21"	Cast	20 to 60	1/4"	6-11/16"	3'6"	6°19'20"	3/8"	5"	4"	11'0"	17'0"	4-7/8"	7'5-1/2"	6'11-1/4"
		WPF	20 to 30	1/4"	17"	3'6"	6°19'20"	3/8"	5"	4"	11'0"	17'0"	3-7/8"	6'7-1/4"	6'1"
		WPF	40 to 60	3/8"	20"	3'6"	6°19'20"	3/8"	5"	4"	11'0"	17'0"	3-9/16"	6'4-1/4"	5'10"
2-1/2	22°37'12"	Cast	20 to 40	1/4"	8-1/4"	5'0"	4°25'15"	3/8"	5"	5"	15'0"	28'0"	5-1/16"	9'8-1/2"	9'3-3/4"
		WPF	20 to 30	1/4"	16-1/2"	5'0"	4°25'15"	3/8"	5"	5"	15'0"	28'0"	4-3/8"	9'0-1/4"	8'7-1/2"
		WPF	40 to 60	3/8"	20"	5'0"	4°25'15"	3/8"	5"	5"	15'0"	28'0"	4-1/16"	8'8-3/4"	8'4"
3	18°55'29"	Cast	20 to 60	1/4"	8-3/8"	5'0"	4°25'15"	3/8"	5"	5"	16'9"	42'0"	4-5/8"	11'4-3/4"	11'0-3/4"
		WPF	20 to 30	1/4"	16-1/2"	5'0"	4°25'15"	3/8"	5"	5"	16'9"	42'0"	4-1/8"	10'8-1/2"	10'4-1/2"
		WPF	40 to 60	3/8"	24"	5'0"	4°25'15"	3/8"	5"	5"	16'9"	42'0"	3-5/8"	10'1"	9'9"
4	14°15'00"	Cast	20 to 60	1/4"	11-1/16"	5'0"	4°25'15"	3/8"	5"	5"	20'0"	78'0"	3-15/16"	14'4"	14'1"
		WPF	40 to 60	3/8"	27"	5'0"	4°25'15"	3/8"	5"	5"	20'0"	78'0"	3-1/4"	13'0-1/4"	12'9"
5	11°25'16"	Cast	20 to 60	1/4"	13-13/16"	7'6"	2°56'44"	3/8"	5"	8"	27'0"	120'0"	4-5/16"	18'6-3/4"	18'4-1/4"
		WPF	40 to 60	3/8"	30"	7'6"	2°56'44"	3/8"	5"	8"	27'0"	120'0"	3-3/4"	17'2-1/2"	17'0"
6	9°31'38"	Cast	20 to 60	1/4"	16-9/16"	7'6"	2°56'44"	3/8"	5"	8"	30'2"	179'0"	3-7/8"	21'5-1/2"	21'3-1/2"
		WPF	40 to 60	3/8"	36"	7'6"	2°56'44"	3/8"	5"	8"	30'2"	179'0"	3-5/16"	19'10"	19'8"
6	9°31'38"	Cast	20 to 60	1/4"	16-9/16"	10'0"	2°12'32"	3/8"	5"	10"	34'0"	171'0"	4-9/16"	22'9-1/2"	22'7-1/2"
		WPF	40 to 60	3/8"	36"	10'0"	2°12'32"	3/8"	5"	10"	34'0"	171'0"	3-15/16"	21'2"	21'0"

Note: WPF denotes "Welded Plate Frog."