

Trackmobile ATLAS



Standard Features		
CAN-Bus Control System with On-board Diagnostics	Accessible External Disc Brakes	
UltraView 7" Color Touch Screen Display	Impact Sensor/Recorder	
Ergonomic Air Ride, High Back 180° Swivel Seat	Embedded LED head lights.	
Joystick and Armrest Controls	LED strobe, work, and under hood lights	
Tinted tempered glass (meets ANSI 26.1 standard)	Upgraded Jumpseat	
Automatic / Manual Power-Shift Transmission	Premium HVAC system	
• 100 CFM Rotary Screw Air Compressor	• 35,000 BTU with 550 CFM HVAC	
In-Cab Front and Rear Train Air Valves	Fire Extinguisher, 5 pounds	
Incremental Train Air Brake Controller	Heavy-duty Mine Service Foam Filled Tires	
Train Air Hold Button	Patented MAX-Tran and MAX-Trac systems	
Steel Railwheels	Train Air Charge Indicator	

Dimensions / Performance**			
	On Rail	On Road	
Wheel Base	157.5" [4,001 mm]	89.2" [2,265.7 mm]	
Rail & Road Clearance	4.8" [122 mm]	13.9" [353 mm]	
Rail & Road Height	149.8" [3,805 mm]	164.6" [4,181 mm]	
Length	220" [5	220" [5,588 mm]	
Width^^	125" [3	125" [3,175 mm]	
Weight	83,500 lbs	83,500 lbs [37,875 kg]	
Rail Gauge*	AAR Standard 5	AAR Standard 56.5" [1,435 mm]	
Centerline to Cab Side	62.6" [1	62.6" [1,590 mm]	
Centerline to Non-Cab Side	62.5" [1	62.5" [1,588 mm]	

Maximum Tractive Effort*		
60,225 lbs [27,318 kg]	Double Coupled	
43,900 lbs [19,913 kg]	Single Coupled	