

Trackmobile VIKING



Standard Features
CAN-Bus Control System with On-board Diagnostics
UltraView 7" Color Touch Screen Display
Safe-T-VueTM 360° Visibility and Railing Display
• Ergonomic Air Ride, High Back 180° Swivel Seat
Joystick and Armrest Controls
Neutral Braking
Programmed Throttle Control with Dual Ramp Rates
Automatic / Manual Power-Shift Transmission
60 CFM Twin Cylinder Air Compressor
In-Cab Front and Rear Train Air Valves
Incremental Train Air Brake Controller
Train Air Hold Button
Steel Railwheels
Impact Sensor/Recorder

Dimensions / Performance**			
	On Rail	On Road	
Wheel Base	121" [3,073 mm]	59.5" [1,511 mm]	
Rail & Road Clearance	3.5" [88.9 mm]	9.3" [236.2 mm]	
Rail & Road Height	148.8" [3,779 mm]	159.4" [4,049 mm]	
Length	152" [3,860 mm]		
Width^^	126.5" [3,213 mm]		
Weight	34,360 lbs [15,585 kg]		
Rail Gauge*	AAR Standard 56.5" [1,435 mm]		
Centerline to Cab Side	65.4" [1,661 mm]		
Centerline to Non-Cab Side	61.1" [1,552 mm]		

Maximum Tractive Effort*		
42,689 lbs [19,363 kg]	Double Coupled	
27,014 lbs [12,253 kg]	Single Coupled	